

SACC-DSIV-M12MSB-5CON-L 90 - Device connector rear mounting



1527867
<https://www.phoenixcontact.com/us/products/1527867>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector rear mounting, 5-position, Pin, angled, M12, coding: B, Rear mounting, M12 x 1, Wave soldering

Commercial data

Item number	1527867
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	AB23
Product key	ABQEGI
Catalog page	Page 60 (PC-2011)
GTIN	4017918984946
Weight per piece (including packing)	11.7 g
Weight per piece (excluding packing)	11.48 g
Customs tariff number	85366990
Country of origin	HU

SACC-DSIV-M12MSB-5CON-L 90 - Device connector rear mounting



1527867

<https://www.phoenixcontact.com/us/products/1527867>

Technical data

Mounting

Mounting type	Rear mounting M12 x 1 With locking nut
Assembly instructions	With locking nut

Product properties

Product type	Circular connectors (device side)
Number of positions	5
Shielded	no
Coding	B
Thread type	M12

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Material specifications

Flammability rating according to UL 94	HB
Seal material	NBR
Contact material	CuZn
Contact surface material	Au
Contact carrier material	PA 6.6
Material for screw connection	Brass, nickel-plated

Electrical properties

Contact resistance	$\leq 3 \text{ m}\Omega$
Insulation resistance	$\geq 100 \text{ M}\Omega$
Nominal voltage U_N	125 V
Nominal current I_N	4 A

Connection data

Conductor connection

Connection method	Wave soldering
Contact connection type	Pin

Connector

Connection 1

Head design	Pin
Head cable outlet	angled
Head thread type	M12
Coding	B

SACC-DSIV-M12MSB-5CON-L 90 - Device connector rear mounting



1527867
<https://www.phoenixcontact.com/us/products/1527867>

Environmental and real-life conditions

Ambient conditions	
Degree of protection	IP67
	IP67
Ambient temperature (operation)	-40 °C ... 85 °C (Plug / socket)

Standards and regulations

M12	
Standard designation	M12 connector
Standards/specifications	IEC 61076-2-101

SACC-DSIV-M12MSB-5CON-L 90 - Device connector rear mounting



1527867
<https://www.phoenixcontact.com/us/products/1527867>

Classifications

ECLASS

ECLASS-11.0	27440102
ECLASS-12.0	27440116
ECLASS-13.0	27440116

ETIM

ETIM 9.0	EC002635
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

SACC-DSIV-M12MSB-5CON-L 90 - Device connector rear mounting



1527867
<https://www.phoenixcontact.com/us/products/1527867>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com